

SAFETY DATA SHEET



CROWN ALLOYS COMPANY

Section 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:	Tool & Die Flux Coated/Cored Rods and Bare Wire																																			
PRODUCT IDENTIFICATION:	<table border="1"> <thead> <tr> <th colspan="2">Tool Steel Electrodes</th> <th colspan="3">Tool Steel TIG</th> <th>Tool Steel MIG</th> </tr> </thead> <tbody> <tr> <td>AH-20</td> <td>HW-20</td> <td>AH-10</td> <td>HS-7-10</td> <td>OH-10</td> <td rowspan="5">FH-30</td> </tr> <tr> <td>CM-86-20</td> <td>NT-HW-20</td> <td>12-AH-10</td> <td>HSS-10</td> <td>PIM-10</td> </tr> <tr> <td>CX-20</td> <td>OH-20</td> <td>CM-86-10</td> <td>HW-10</td> <td>WH-10</td> </tr> <tr> <td>FH-20</td> <td>WH-20</td> <td>FH-10</td> <td>12-HW-10</td> <td>2-25-10</td> </tr> <tr> <td>HSS-20</td> <td></td> <td>12-FH-10</td> <td>NT-HW-10</td> <td>MAR 301-10</td> </tr> </tbody> </table>	Tool Steel Electrodes		Tool Steel TIG			Tool Steel MIG	AH-20	HW-20	AH-10	HS-7-10	OH-10	FH-30	CM-86-20	NT-HW-20	12-AH-10	HSS-10	PIM-10	CX-20	OH-20	CM-86-10	HW-10	WH-10	FH-20	WH-20	FH-10	12-HW-10	2-25-10	HSS-20		12-FH-10	NT-HW-10	MAR 301-10			
Tool Steel Electrodes		Tool Steel TIG			Tool Steel MIG																															
AH-20	HW-20	AH-10	HS-7-10	OH-10	FH-30																															
CM-86-20	NT-HW-20	12-AH-10	HSS-10	PIM-10																																
CX-20	OH-20	CM-86-10	HW-10	WH-10																																
FH-20	WH-20	FH-10	12-HW-10	2-25-10																																
HSS-20		12-FH-10	NT-HW-10	MAR 301-10																																
SPECIFICATION:	AISI A-2, 8620, 4130, M-2, H-12, H-13, O-1, W-2		AISI A-2, D-2, 8620, 4130, 6150, S-7, M-2, H-12, H-13, O-1, P-20, W-2			AISI 4130																														
RECOMMENDED USE:	SMAW (Shielded Metal Arc Welding), GTAW (Gas Tungsten Arc Welding) and GMAW (Gas Metal Arc Welding)																																			
SUPPLIER:	Crown Alloys Company 30105 Stephenson Hwy. Madison Heights, MI. 48071																																			
TELEPHONE NUMBER:	(248) 588-3790																																			
EMERGENCY NUMBER:	Call CHEMTREC Day or Night 1-800-424-9300 / +1 703-527-3887																																			
WEBSITE:	www.crownalloys.com																																			

Section 2 – HAZARDS IDENTIFICATION

2.1 Classification of the mixture

This product is placed on the market in solid form

2.1.1 Classification in accordance with GHS-US

Health, Skin corrosion/irritation, 1	Health, Carcinogenicity, 1
Health, Specific target organ toxicity – Single exposure, 3	Health, Specific target organ toxicity – Repeated exposure, 2

2.2 Label elements

GHS-US labelling

Hazard Pictograms (GHS-US):



GHS07



GHS08



GHS09

Signal word (GHS-US):

Danger

Hazard statements (GHS-US):

- | | |
|--|---|
| H302 – Harmful if swallowed | H335 – May cause respiratory irritation |
| H314 – Causes severe skin burns and eye damage | H336 – May cause drowsiness or dizziness |
| H315 – Causes skin irritation | H350 – May cause cancer |
| H317 – May cause an allergic skin reaction | H372 – Causes damage to organs through prolonged or repeated exposure |
| H319 – Causes serious eye irritation | H400 – Very toxic to aquatic life |
| CGA-HG11 – SYMPTOMS MAY BE DELAYED | |

Precautionary statements (GHS-US):

- | | |
|--|--|
| P201 – Obtain special instructions before use | P308+P313 – IF EXPOSED OR CONCERNED: Get medical advice/attention |
| P202 – Do not handle until all safety precautions have been read and understood | P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing |
| P232 – Protect from moisture | P312 – Call a POISON CENTER or physician if you feel unwell |
| P260 – Do not breathe dust/fume/gas/mist/vapors/spray | P314 – Get medical advice and attention if you feel unwell |
| P261 – Avoid breathing dust/fume/gas/mist/vapors/spray | P321 – Specific treatment (see label) |
| P264 – Wash thoroughly after handling | P333+P313 – If skin irritation or rash occurs: Get medical advice/attention |
| P270 – Do not eat, drink or smoke when using this product | P362+P364 – Take off contaminated clothing and wash it before reuse |
| P271 – Use only outdoors or in a well-ventilated area | P403+P233 – Store in a well-ventilated place. Keep container tightly closed |
| P272 – Contaminated work clothing should not be allowed out of the workplace | P405 – Store locked up |
| P280 – Wear protective gloves/protective clothing/eye protection/face protection | P501- Dispose of contents/container in accordance with local / regional / national / international regulations |
| P302+P352 – IF ON SKIN: Wash with plenty of soap and water | CGA-PG27 – Read and follow the Safety Data Sheet (SDS) before use |

2.3 Other hazards

No additional information available

2.4 Unknown acute toxicity (GHS-US)

No data available



CROWN ALLOYS COMPANY

SAFETY DATA SHEET

Other hazards which do not result in GHS classification:

Electrical shock can kill.
 Arc rays can injure eyes and burn skin.
 Welding arc and sparks can ignite combustibles and flammable materials.
 Overexposure to welding fumes and gases can be hazardous.
 Read and understand the manufacturer's instructions, Safety Data Sheets and the precautionary labels before using these alloys. Refer to Section 8.

Substance(s) formed under the conditions of use:

The welding fumes produced from these welding alloys may contain the following constituent(s) and/or their complex metallic oxides as well as solid particles or other constituents from the consumables, base metal, or base metal coating not listed below:

Chemical Identity	CAS-No.	Chemical Identity	CAS-No.	Chemical Identity	CAS-No.
Carbon Dioxide	124-38-9	Ozone	10028-15-6	Manganese	7439-96-5
Carbon Monoxide	630-08-0	Nitrogen Dioxide	10102-44-0	Chromium Oxide	1308-38-9
Nickel	7440-02-0	Chromium (VI)	18540-29-9	Cobalt	7440-48-4

Section 3 – COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

Full text of H-phrases: See section 16

3.2 Mixture

Reportable Hazardous Ingredients

Chemical Identity	CAS-No.	Weight Percent (%)	GHS-US Classification
Aluminum and/or aluminum alloys (as Al)	7429-90-5	1.80 max.	Comb. Dust
Carbon (C)	7440-44-0	0.05 – 1.60	Not classified
Chromium (Cr)	7440-47-3	0.05 – 28.0	Comb. Dust
Cobalt (Co)	7440-48-4	8.50 max.	Acute Tox. 4 (Oral), H302 Acute dust/mist 1, H330 Eye Irrit. 2A, H319 Resp. Sens. 1B, H334 Skin Sens. 1, H317 Carc. 1B, H350 Repro. tox. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Iron (Fe)	7439-89-6	35.0 – 98.0	Acute Tox. 4 (Oral), H302
Manganese compounds and fumes (as Mn)	7439-96-5	0.05 – 3.25	Not classified
Molybdenum soluble and insoluble compounds (as Mo)	7439-98-7	0.005 – 10.0	Not classified
Nickel (Ni)	7440-02-0	22.0 max.	Skin Sens. 1, H317 Carc. 1B, H350 STOT RE 1, H372
Niobium (Nb)	7440-03-1	2.00 max.	Not classified
Silicon (Si)	7440-21-3	0.05 – 1.60	Not classified
Titanium (Ti)	7440-32-6	10.0 max.	Not classified
Tungsten metal powder (W)	7440-33-7	0.005 – 10.0	Not classified
Vanadium pentoxide dust and fume (V)	1314-62-1	2.50 max.	Not classified
*Bentonite (clay)	1302-78-9	6.00 max.	Not classified
*Calcium carbonate, limestone (CaCO ₃)	1317-65-3	50.0 max.	Not classified
*Calcium fluoride (CaF ₂)	7789-75-5	20.0 max.	Acute Tox. Not classified (Oral)
*Cellulose, carboxymethyl ether, sodium salt	9004-32-4	5.00 max.	Not classified
*Cryolite	1506-52-3	2.00 max.	Not classified
*Ethanedioic acid, dipotassium salt	583-52-8	1.50 max.	Not classified
*Iron oxide (Fe ₂ O ₃)	1309-37-1	8.00 max.	Acute Tox. 4 (Oral), H302
*Magnesium oxide (MgO)	1309-48-4	15.0 max.	Not classified
*Potassium silicate (K ₂ O ₃ SiO ₃)	1312-76-1	1.00 max.	Acute Tox. 4 (Oral), H302
*Silica, amorphous	7631-86-9	5.00 max.	Not classified
*Silica, crystalline	14808-60-7	5.00 max.	Eye Irrit. 2B, H320 Carc. 1A, H350 STOT SE 3, H335 STOT RE 2, H373
*Silicic acid, potassium salt	1312-76-1	10.0 max.	Acute Tox. 4 (Oral), H302
*Sodium silicate (Na ₂ O-NSiO ₂)	1344-09-8	5.00 max.	Acute Tox. 4 (Oral), H302
*Strontium carbonate	7440-24-6	1.00 max.	Not classified
*Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6	5.00 max.	Not classified
*Titanate, dipotassium (KTiO ₃)	12030-97-6	10.0 max.	Not classified
*Titanium dioxide (TiO ₂)	13463-67-7	15.0 max.	Carc. 2, H351
*Zirconium silicate	14940-68-2	5.00 max.	Not classified

*Flux Constituent. The "Weight Percent" values are for the flux coating or flux core only.

Composition Comments:

The term "Hazardous Ingredients" should be interpreted as a term defined in Hazard Communication standards and does not necessarily imply the existence of a welding hazard. These alloys may contain additional non-hazardous ingredients or may form additional compounds under the condition of use. Refer to Sections 2 & 8 for more information.

SAFETY DATA SHEET



CROWN ALLOYS COMPANY

Section 4 – FIRST AID MEASURES

4.1 Description of first aid measures

Ingestion:	Unlikely due to the form of the product. Avoid hand, clothing, food, and drink contact with metal fume or powder which can cause ingestion of particulate during hand to mouth activities such as drinking, eating, smoking, etc. If ingested, do not induce vomiting. Contact a poison control center. Unless the poison control center advises otherwise, wash out mouth thoroughly with water. If symptoms develop, seek medical attention at once.
Inhalation:	Move to fresh air if breathing is difficult. If not breathing, perform artificial respiration. Seek medical assistance immediately.
Skin Contact:	Flush with soap and water for at least 15 minutes. For reddened or blistered skin, or thermal burns, obtain medical assistance.
Eye Contact:	Dust or fume from these alloys should be flushed from the eyes with clean, tepid water until transported to a medical facility. Do not rub eyes or keep eyes tightly closed. Obtain immediate medical assistance. Arc rays can injure eyes. If exposed, move victim to a dark room, remove contact lenses and cover eyes with a padded dressing and rest. Obtain medical assistance if symptoms persist.

4.2 Most important symptoms/effects, acute and delayed

Symptoms/injuries after inhalation:	Short-term (acute) overexposure to the gases, fumes, and dusts may include irritation of the eyes, lungs, nose, and throat. Some toxic gases associated with welding may cause pulmonary edema, asphyxiation, and death. Acute overexposure may include signs and symptoms such as watery eyes, nose and throat irritation, headache, dizziness, difficulty in breathing, frequent coughing, or chest pain. The presence of chromium/chromate in fume can cause irritation of nasal membranes and skin. The presence of nickel compounds in fume can cause metallic taste, nausea, tightness of chest, fever, and allergic reaction. Excessive inhalation or ingestion of manganese can produce manganese poisoning. Overexposure to manganese compounds may affect the central nervous system, symptoms of which are languor, sleepiness, muscular weakness, emotional disturbances, and spastic gait resembling Parkinsonism. These symptoms can become progressive and permanent if not treated. Excessive inhalation of fumes may cause "Metal Fume Fever" with Flu-like symptoms such as chills, fever, body aches, vomiting, sweating, etc.
Symptoms/injuries after skin contact:	Dusts may cause irritation.
Symptoms/injuries after eye contact:	Causes eye irritation.
Symptoms/injuries after ingestion:	Not an anticipated route of exposure during normal product handling. May be harmful if ingested.

4.3 Indication of immediate medical attention and special treatment needed

No additional information available

Section 5 – FIRE-FIGHTING MEASURES

General Fire Hazards: As shipped, this product is nonflammable. However, welding arc and sparks can ignite combustibles and flammable products. Read and understand American National Standard Z49.1, "Safety In Welding, Cutting and Allied Processes" and National Fire Protection Association NFPA 51B, "Standard for Fire Prevention During Welding, Cutting and Other Hot Work" before using this product.

5.1 Extinguishing media

Suitable extinguishing media:	Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media:	None known.

5.2 Special hazards arising from the substance

Fire hazard:	Not flammable.
Explosion hazard:	None known.

5.3 Special protective equipment and precautions for firefighters

Special firefighting procedures:	Use standard firefighting procedures and consider the hazards of other involved materials.
Special protective equipment for firefighters:	Firefighters should wear full protective gear.

Section 6 – ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

If airborne dust and/or fume is present, use adequate engineering controls and, if needed, personal protection to prevent overexposure. Refer to recommendations in Section 8.

6.2 Environmental precautions

Avoid release to the environment

6.3 Methods and material for containment and cleaning up

Clean up spills immediately, observing precautions in the personal protective equipment in Section 8. Avoid generating dust. Prevent product from entering any drains, sewers or water sources. Refer to Section 13 for proper disposal. Attempt to reclaim the product if possible.

SAFETY DATA SHEET



CROWN ALLOYS COMPANY

Section 7 – HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid inhaling welding fumes. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Read and understand the manufacturer's instruction and the precautionary label on the product. See American National Standard Z49.1, "Safety In Welding, Cutting and Allied Processes" published by the American Welding Society, <http://pubs.aws.org> and OSHA Publication 2206 (29CFR1910), U.S. Government Printing Office, www.gpo.gov.

7.2 Conditions for safe storage, including any incompatibilities

Store in closed original container in a dry place. Store away from incompatible materials. Store in accordance with local/regional/national regulations.

7.3 Specific end use(s)

For welding consumables and related products

Section 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Chemical Identity (CAS-No.)	ACGIH TLV (TWA)	OSHA PEL (TWA)	NIOSH REL	NIOSH STEL
Aluminum (7429-90-5)	1 mg/m ³ (respirable fraction)	5 mg/m ³ (respirable dust as Al) 15 mg/m ³ (total dust as Al)	5 mg/m ³ (respirable) 10 mg/m ³ (total)	N/A
Chromium (7440-47-3)	0.5 mg/m ³ [metal compound as Cr] 0.05 mg/m ³ [Cr(VI) inorganic compounds as Cr, water soluble] 0.01 mg/m ³ [Cr(VI) inorganic compounds as Cr, water insoluble]	1.0 mg/m ³ [metal compound as Cr] 0.005 mg(5 µg)/m ³ [Cr(VI) inorganic compounds as Cr(VI), water soluble] 0.005 mg(5 µg)/m ³ [Cr(VI) inorganic compounds as Cr(VI), insoluble]	0.5 mg/m ³	N/A
Cobalt (7440-48-4)	0.02 mg/m ³	0.01 mg/m ³	0.05 mg/m ³	N/A
Iron (7439-89-6)	5.0 mg/m ³ (as Fe ₂ O ₃) respirable fraction	10.0 mg/m ³ (fume, as Fe ₂ O ₃)	N/A	N/A
Manganese (7439-96-5)	0.02 mg/m ³ (elemental and inorganic compounds, as Mn – respirable fraction) 0.1 mg/m ³ (elemental and inorganic compounds, as Mn – inhalable fraction)	5.0 mg/m ³ (fume, as Mn) Ceiling	1 mg/m ³	3 mg/m ³
Molybdenum (7439-98-7)	3.0 mg/m ³ (respirable fraction, as Mo) 10.0 mg/m ³ (inhalable fraction, as Mo)	15.0 mg/m ³ (total dust, as Mo)	N/A	N/A
Nickel (7440-02-0)	1.5 mg/m ³ as metal (inhalable fraction)	1.0 mg/m ³ (metal and insoluble compounds as Ni)	0.015 mg/m ³	N/A
Silicon (7440-21-3)	Withdrawn	15.0 mg/m ³ (total dust) 5.0 mg/m ³ (respirable fraction)	5.0 mg/m ³ (respirable) 10.0 mg/m ³ (total)	N/A
Titanium (7440-32-6)	10 mg/m ³ as oxide dust	15 mg/m ³ as oxide dust (total particulate)	N/A	N/A
Tungsten (7440-33-7)	5.0 mg/m ³	5.0 mg/m ³	5.0 mg/m ³	10.0 mg/m ³
Vanadium Pentoxide (1314-62-1)	0.05 mg/m ³	0.05 mg/m ³	N/A	N/A
Bentonite, clay (1302-78-9)	5.0 mg/m ³	5.0 mg/m ³ (dust)	N/A	N/A
Calcium Carbonate (1317-65-3)	10.0 mg/m ³	15.0 mg/m ³ (dust)	N/A	N/A
Calcium Fluoride (7789-75-5)	2.5 mg/m ³	2.5 mg/m ³ (as F)	N/A	N/A
Cellulose (9004-32-4)	10.0 mg/m ³	10.0 mg/m ³	N/A	N/A
Cryolite (1506-52-3)	3.0 mg/m ³	10.0 mg/m ³	N/A	N/A
Magnesium Oxide (1309-48-4)	10.0 mg/m ³ (fume)	15.0 mg/m ³	N/A	N/A
Potassium Silicate (1312-76-1)	5.0 mg/m ³	15.0 mg/m ³	N/A	N/A
Silica, crystalline (14808-60-7)	0.025 mg/m ³ (respirable fraction)	0.01 mg/m ³ 0.30 mg/m ³ (total dust)	0.05 mg/m ³ (respirable dust)	N/A
Talc (14807-96-6)	2.0 mg/m ³	2.0 mg/m ³	N/A	N/A
Titanate, dipotassium (12030-97-6)	2.5 mg/m ³	2.5 mg/m ³ (dust)	N/A	N/A
Titanium Dioxide (13463-67-7)	10.0 mg/m ³	10.0 mg/m ³	N/A	N/A
Zirconium Silicate (14940-68-2)	10.0 mg/m ³	5.0 mg/m ³	N/A	N/A

SAFETY DATA SHEET



CROWN ALLOYS COMPANY

8.2 Exposure controls

Appropriate Engineering Controls:

Use enough ventilation, local exhaust at the arc, or both to keep the fumes and gases from the worker's breathing zone & the general area. Maintain exposures below acceptable exposure levels (see Section 8.1). Use industrial hygiene air monitoring to ensure that your use of these products does not create exposures that exceed the recommended exposure limits. Always use exhaust ventilation in user operations such as high temperature cutting, grinding, welding and brazing. Train the welder to keep his head out of the fume plume. Confined spaces require adequate ventilation and/or air supplied respirators. Read and understand the manufacturer's instructions and the precautionary label on the product. See American National Standard Z49.1, Safety in Welding, Cutting, and Allied Processes, published by the American Welding Society, 8669 Doral Blvd. Suite 130, Doral, FL 33166 and OSHA Publication 2206 (29CFR1910), US Government Printing Office, Washington, D.C. 20402 for more details on many of the following.

General information:

Exposure Guidelines: Threshold Limit Values (TLVs) and Biological Exposure Indices (BEIs) are values published by the American Conference of Government Industrial Hygienists (ACGIH). ACGIH Statement of Positions Regarding the TLVs® and BEIs® states that the TLV-TWA should be used as a guide in the control of health hazards and should not be used to indicate a fine line between safe and dangerous exposures. See Section 10 for information on potential fume constituents of health interest. Threshold Limit Values are figures published by the American Conference of Government Industrial Hygienists.

Eye/face protection:

Wear helmet or use face shield with filter lens shade number 12 or darker for open arc processes. No specific lens shade recommendation for submerged arc processes. Shield others by providing screens and flash goggles.

Skin/Hand Protection:

Wear protective gloves. Suitable gloves can be recommended by the glove supplier.

Protective Clothing:

Wear hand, head, and body protection which help to prevent injury from radiation, sparks and electrical shock. See Z49.1. At a minimum this includes welder's gloves and a protective face shield, and may include arm protectors, aprons, hats, shoulder protection, as well as dark substantial clothing. Wear dry gloves free of holes or split seams. Train the welder not to permit electrically live parts or electrodes to contact skin . . . or clothing or gloves if they are wet. Insulate yourself from the work piece and ground using dry plywood, rubber mats or other dry insulation.

Respiratory Protection:

Keep your head out of fumes. Use enough ventilation and local exhaust to keep fumes and gases from your breathing zone and the general area. An approved respirator should be used unless exposure assessments are below applicable exposure limits. Use respirable fume respirator or air supplied respirator when welding in confined space or where local exhaust or ventilation does not keep exposure below TLV's (see Section 8.1). Use only NIOSH approved respirators in accordance with 29 CFR 1910.134 – Respiratory Protection. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998).

Hygiene measures:

Do not eat, drink or smoke when using the product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Cosmetics should not be applied in areas where exposures exist! Routinely wash work clothing and protective equipment to remove contaminants.

Determine the composition and quantity of fumes and gases to which workers are exposed by taking an air sample from inside the welder's helmet if worn or in the worker's breathing zone. Improve ventilation if exposures are not below limits. See ANSI/AWS F1.1, F1.2, F1.3 and F1.5, available from the American Welding Society, www.aws.org.

Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Solid or flux cored or flux coated welding wire or rod
Physical state	Solid
Form	Solid
Color	Metallic
Odor	None
Odor threshold	No data available
pH	Not applicable
Melting point/freezing point	No data available
Flammability (solid, gas)	No data available
Flash Point	Not applicable
Evaporation rate	Not applicable
Initial boiling point and boiling range	No data available

Flammability limit - upper (%)	No data available
Flammability limit - lower (%)	No data available
Explosive limit - upper (%)	No data available
Explosive limit - lower (%)	No data available
Vapor pressure	Not applicable
Vapor density	Not applicable
Relative density	No data available
Solubility in water	None
Solubility (other)	No data available
Partition coefficient (n-octanol/water)	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	Not applicable

Section 10 – STABILITY AND REACTIVITY

10.1 Reactivity

This product is non-reactive under normal conditions of use, storage and transport.

10.2 Chemical stability

This product is stable under normal conditions.

10.3 Possibility of hazardous reactions

Will not occur.

10.4 Conditions to avoid

Uncontrolled exposure to extreme temperatures and/or contamination.

SAFETY DATA SHEET



10.5 Incompatible materials

Strong acids, strong oxidizers, mineral acids, some halogenated compounds, phosphorus and mercury.

10.6 Hazardous decomposition products

Welding/brazing fumes and gases can't be classified simply. The composition and quantity of both are dependent upon the metal being welded/brazed and the rods used. Coatings on the metal being welded/brazed (such as paint, plating, or galvanizing), the number of welders, the volume of the work area, the quality and the amount of ventilation, the position of the welder's head with respect to the gas plume, the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing activities), the process and procedures, as well as the welding/brazing consumables.

When these tool steel rods/wires are consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 3. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 3, plus those from the base metal, coatings, etc., as noted above. Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from an arc, in addition to the shielding gases like argon and helium, whenever they are employed. Reasonably expected fume constituents of these tool steel rods/wires would include: Complex oxides of iron, aluminum, manganese, nickel, calcium, niobium, molybdenum, silicon, chromium, titanium, carbon dioxide, carbon monoxide, ozone and nitrogen oxides. Fluorides will also be present. Some products may also contain cobalt, magnesium, strontium, tungsten, and/or zirconium. The fume limit for chromium, cobalt, nickel, vanadium, calcium fluoride, silica (crystalline) and/or manganese may be reached before the general welding fume limit of 5 mg/m³ is reached. One recommended way to determine the composition and quantity of fumes and gases to which workers are exposed is to take an air sample inside the welder's helmet if worn or in the worker's breathing zone. See ANSI/AWS F1.1 "Method for Sampling Airborne Particles Generated by Welding and Allied Processes" and "Characterization of Arc Welding Fume" available from the American Welding Society, 8669 Doral Blvd. Suite 130, Doral, FL 33166.

A SIGNIFICANT AMOUNT OF THE CHROMIUM IN THE FUMES CAN BE HEXAVALENT CHROMIUM , ALSO KNOWN AS Cr(VI), WHICH HAS A VERY LOW EXPOSURE LIMIT OF 0.005 mg/m³ (5 µg/m³).

Monitor fume levels and Cr(VI) level. Train workers about the hazards of Cr(VI). Read and comply with OSHA's permissible exposure limits for hexavalent chromium Cr(VI), Fed. Reg. 71 – 10099 (specifically 29 CFR 1910.1026, 29 CFR 1915.1026, and 29 CFR 1926.1126). For Cr(VI), OSHA requires: "The employer shall perform initial monitoring to determine the 8-hour TWA exposure for each employee on the basis of a sufficient number of personal breathing zone air samples to accurately characterize full shift exposure on each shift, for each job classification, in each work area". Specialized equipment is required for monitoring Cr(VI) concentration in the workplace. OSHA Analytical Method Number ID-215 for area and breathing zone sampling and OSHA Analytical Method Number W4001 for wipe samples are listed on the OSHA website – www.osha.gov – as methods for measuring Cr(VI). This standard is complex and the employer should contact an occupational health professional for doing the Cr(VI) monitoring and all other fume monitoring.

EU RoHS (European Union Restriction of Hazardous Substances): Some of these tool steel rods/wires contain Chromium. During welding these alloys will produce Cr(VI) (hexavalent chromium), however, the weld deposit does not contain Cr(VI) as it will all be in the zero valent state or as Cr(III) as an oxide. FINISHED PRODUCTS MANUFACTURED USING THESE TOOL STEEL RODS/WIRES WILL NOT CONTAIN ANY Cr(VI).

Section 11 – TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

- Ingestion:** Health injuries from ingestion are not known or expected under normal use.
- Inhalation:** Potential chronic health hazards related to the use of welding consumables are most applicable to the inhalation route of exposure. Refer to Inhalation statements in this section.
- Skin Contact:** Arc rays can burn skin. Skin cancer has been reported.
- Eye contact:** Arc rays can injure eyes.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation:** Short-term (acute) overexposure to welding fumes may result in discomfort such as metal fume fever, dizziness, nausea, or dryness or irritation of nose, throat, or eyes. May aggravate pre-existing respiratory problems (e.g. asthma, emphysema). Long-term (chronic) overexposure to welding fumes can lead to siderosis (iron deposits in lung), central nervous system effects, bronchitis and other pulmonary effects. Respiratory exposure to the crystalline silica that is in some of these tool steel welding rods/wires is not anticipated during normal use. Respiratory overexposure to airborne crystalline silica is known to cause silicosis, a form of disabling pulmonary fibrosis which can be progressive and may lead to death. Crystalline silica is on the IARC and NTP lists as posing a cancer risk to humans.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure): Harmful if swallowed

Specified substance: IRON LD50 (oral, rat) = 98.6 g/kg ATE (oral) = 984.00 mg/kg	Specified substance: MANGANESE LD50 (oral, rat) = 9000 mg/kg ATE (oral) = 9000000.0 mg/kg	Specified substance: SILICON ATE (oral) = 3160.0 mg/kg LD50 (oral, rat) = 3160 mg/kg
Specified substance: NICKEL LD50 (oral, rat) > 9000 mg/kg	Specified substance: TITANIUM DIOXIDE LD50 (oral, rat) >10000 mg/kg	Specified substance: CARBON LD50 (oral, rat) > 10000 mg/kg
Specified substance: CALCIUM FLUORIDE LD50 (oral, rat) = 4250 mg/kg ATE (oral) = 4250.00 mg/kg bodyweight	Specified substance: POTASSIUM SILICATE LD50 (oral, rat) = 1300 mg/kg ATE (oral) = 1300.00 mg/kg bodyweight	Specified substance: SODIUM SILICATE LD50 (oral, rat) = 1153 mg/kg ATE (oral) = 1153.00 mg/kg
Specified substance: COBALT LD50 (oral, rat) = 215.9 – 1140 mg/kg LC50 (inhalation, rat, 1h) > 10 mg/l ATE (oral) = 215.90 mg/kg ATE (dust/mist, 4h) = 0.01 mg/l	Specified substance: VANADIUM PENTOXIDE LD50 (oral, rat) = 221.1 – 715.7 mg/kg LD50 (dermal, rabbit) = 50 mg/kg LC50 (inhalation, rat) = 2.21 mg/l / 4h	Specified substance: SILICA, CRYSTALLINE LD50 (oral, rat) = 500 mg/kg ATE (oral) = 500.00 mg/kg

- Repeated dose toxicity (product):** Not classified
- Skin corrosion/irritation (product):** Causes skin irritation
- Serious eye damage/irritation (product):** Causes serious eye irritation
- Respiratory or skin sensitization (product):** May cause an allergic skin reaction
- Germ cell mutagenicity (product):** Not classified

SAFETY DATA SHEET



Carcinogenicity (product): May cause cancer

Chromium (7440-47-3)	
International Agency for Research on Cancer (IARC) Monographs	3 (Not classifiable as to its carcinogenicity to humans)
Vanadium Pentoxide (1314-62-1)	
International Agency for Research on Cancer (IARC) Monographs	2B (Possibly carcinogenic to humans)
National Toxicology Program (NTP) Status	1
Nickel (7440-02-0)	
International Agency for Research on Cancer (IARC) Monographs	2B (Possibly carcinogenic to humans)
National Toxicology Program (NTP) Status	Reasonably anticipated to be a Human Carcinogen
Titanium Dioxide (13463-67-7)	
International Agency for Research on Cancer (IARC) Monographs	2B (Possibly carcinogenic to humans)
Silica, Crystalline [Quartz] (14808-60-7)	
International Agency for Research on Cancer (IARC) Monographs	1 (Carcinogenic to humans)
National Toxicology Program (NTP) Status	2 (Known To Be Human Carcinogen)

Reproductive toxicity (product): Not classified
Specific target organ toxicity - single exposure (product): May cause drowsiness or dizziness. May cause respiratory irritation.
Specific target organ toxicity - repeated exposure (product): Causes damage to organs through prolonged or repeated exposure
Aspiration hazard (product): Not classified

Other Effects: Organic polymers may be used in the manufacture of various welding consumables. Overexposure to their decomposition byproducts may result in a condition known as polymer fume fever. Polymer fume fever usually occurs within 4 to 8 hours of exposure with the presentation of flu like symptoms, including mild pulmonary irritation with or without an increase in body temperature. Signs of exposure can include an increase in white blood cell count. Resolution of symptoms typically occurs quickly, usually not lasting longer than 48 hours.

Symptoms related to the physical, chemical and toxicological characteristics under the condition of use:

<p>Specified substance: CHROMIUM (VI) Inhalation: Chromates may cause ulceration, perforation of the nasal septum, and severe irritation of the bronchial tubes and lungs. Liver damage and allergic reactions, including skin rash, have been reported. Asthma has been reported in some sensitized individuals. Skin contact may result in irritation, ulceration, sensitization, and contact dermatitis. Chromates contain the hexavalent form of chromium [Chromium (VI)]. Hexavalent chromium and its compounds are on the IARC and NTP lists as posing a cancer risk to humans. Specified substance: COBALT Inhalation: Repeated overexposure to cobalt compounds can produce reduced pulmonary function, diffuse nodular fibrosis of lungs and respiratory hypersensitivity.</p>	<p>Specified substance: MANGANESE Inhalation: Overexposure to manganese fumes may affect the brain and central nervous system, resulting in poor coordination, difficulty speaking, and arm or leg tremors. This condition can be irreversible. Specified substance: NICKEL Inhalation: Nickel and its compounds are on the IARC and NTP lists as posing respiratory cancer risk, and are skin sensitizers with symptoms ranging from slight itch to severe dermatitis. Specified substance: FLUORIDES Inhalation: Short term effects from overexposure can cause skin and eye burns, pulmonary edema and bronchitis. Long term effects can result in serious bone erosion (osteoporosis) and mottling of teeth.</p>
--	--

Additional toxicological information under the conditions of use:

Acute toxicity

<p>Specified substance: CHROMIUM (VI) LD50 (oral, rat) = 27 – 59 mg/kg LC50 (inhalation, rat) = 33 – 70 mg/m³/4h</p>	<p>Specified substance: CARBON DIOXIDE LCLo (inhalation, human) = 90000 ppm/5 min. Specified substance: CARBON MONOXIDE LC50 (inhalation, rat) = 1300 mg/l /4h</p>	<p>Specified substance: NITROGEN DIOXIDE LC50 (inhalation, rat) = 88 ppm/4h Specified substance: OZONE LCLo (inhalation, human) = 50 ppm/30 min.</p>
--	---	---

Carcinogenicity:

Specified substance: Chromium (VI) or Hexavalent Chromium	
International Agency for Research on Cancer (IARC) Monographs	1 (Carcinogenic to humans)
National Toxicology Program (NTP) Status	Known to be human carcinogen
US OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Cancer
Specified substance: Chromium Oxide	
International Agency for Research on Cancer (IARC) Monographs	3 (Not classifiable as to its carcinogenicity to humans)
Specified substance: Nickel	
International Agency for Research on Cancer (IARC) Monographs	2B (Possibly carcinogenic to humans)
National Toxicology Program (NTP) Status	Reasonably anticipated to be a Human Carcinogen
Silica, Crystalline [Quartz] (14808-60-7)	
International Agency for Research on Cancer (IARC) Monographs	1 (Carcinogenic to humans)
National Toxicology Program (NTP) Status	2 (Known To Be Human Carcinogen)
Titanium Dioxide (13463-67-7)	
International Agency for Research on Cancer (IARC) Monographs	2B (Possibly carcinogenic to humans)
Vanadium Pentoxide (1314-62-1)	
International Agency for Research on Cancer (IARC) Monographs	2B (Possibly carcinogenic to humans)
National Toxicology Program (NTP) Status	1

SAFETY DATA SHEET



CROWN ALLOYS COMPANY

Section 12 – ECOLOGICAL INFORMATION

Ecotoxicity

Acute hazards to the aquatic environment:

Fish

Specified substance: ALUMINUM and/or aluminum alloys (as Al) LC50 (Grass carp, white amur (Ctenopharyngodon idella), 96 h): 0.21 – 0.31 mg/l	Specified substance: COBALT LC50 (Brachydanio rerio) [static], 96 h): >100 mg/l LOEC (Daphnia Magna): 5.6 mg/l LC50 (Daphnia Magna): >100 mg/l
Specified substance: IRON and/or iron alloys (as Fe) LC50 (Cyprinus carpio) [semi-static], 96 h): 0.56 mg/l	Specified substance: MOLYBDENUM LC50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 800 mg/l
Specified substance: NICKEL LC50 (Fathead minnow (Pimephales promelas), 96 h): 2.916 mg/l LC50 (Brachydanio rerio), 96 h): >100 mg/l EC50 (Daphnia magna), 48 h): >100 mg/l LC50 (Cyprinus carpio) [semi-static], 96 h): 1.3 mg/l EC50 (Daphnia magna) [static], 48 h): 1 mg/l	Specified substance: SODIUM SILICATE LC50 (Western mosquitofish (Gambusia affinis), 96 h): 1,800 mg/l LC50 (Lepomis macrochirus), 96 h): 301 - 478 mg/l LC50 (Brachydanio rerio) [semi-static] 96 h): 3185 mg/l
Specified substance: POTASSIUM SILICATE LC50 (Lepomis macrochirus), 96 h): 301 - 478 mg/l LC50 (Brachydanio rerio) [semi-static] 96 h): 3185 mg/l	

Aquatic Invertebrates

Specified substance: NICKEL EC50 (Water flea (Daphnia magna), 48 h): 1 mg/l EC50 (Pseudokirchneriella subcapitata), 72 h): 0.18 mg/l EC50 (Pseudokirchneriella subcapitata) [static], 96 h): 0.174 – 0.311 mg/l	Specified substance: SODIUM SILICATE EC50 (Water flea (Ceriodaphnia dubia), 48 h): 22.94 – 49.01 mg/l
	Specified substance: MANGANESE EC50 (Water flea (Daphnia magna), 48 h): 40 mg/l

Chronic hazards to the aquatic environment:

Fish (product):	Not classified
Aquatic Invertebrates (product):	Not classified
Toxicity to Aquatic Plants:	Not classified

Persistence and Degradability

Biodegradation (product): No data available

Bioaccumulative Potential

Bioconcentration Factor (BCF) (product): No data available

Specified substance: NICKEL

Zebra mussel (Dreissena polymorpha), Bioconcentration Factor (BCF): 5,000 – 10,000 (Lotic) Bioconcentration factor calculated using dry weight tissue conc.

Mobility in Soil: No data available

Section 13 – DISPOSAL CONSIDERATIONS

Waste disposal recommendations: Prevent waste from contaminating surrounding environment. Discard any product, residue, disposable container or liner in an environmentally acceptable manner, in full compliance with international/federal/state/local regulations. However, alloy wastes are normally collected to recover metal values.

Section 14 – TRANSPORT INFORMATION

In accordance with DOT / ADR / RID / ADNR / IMDG / ICAO / IATA

14.1 UN number

Not a dangerous good in sense of transport regulations

14.2 UN proper shipping name

Not applicable

14.3 Additional information

Other information: No supplementary information available

Overland transport:

No additional information available

Transport by sea:

No additional information available

Air transport:

No additional information available

SAFETY DATA SHEET



Section 15 – REGULATORY INFORMATION

15.1 US Federal regulations

Chromium (7440-47-3) Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings) SARA Section 313 - Emission Reporting: 1.0 %	Aluminum (7429-90-5) Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings) SARA Section 313 - Emission Reporting: 1.0 % (dust or fume only)
Cobalt (7440-48-4) Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings) SARA Section 313 - Emission Reporting: 0.1 %	Manganese (7439-96-5) Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings) SARA Section 313 - Emission Reporting: 1.0 %
Iron (7439-89-6) Listed on the United States TSCA (Toxic Substances Control Act) inventory	Carbon (7440-44-0) Listed on the United States TSCA (Toxic Substances Control Act) inventory
Titanium (7440-32-6) Listed on the United States TSCA (Toxic Substances Control Act) inventory	Silicon (7440-21-3) Listed on the United States TSCA (Toxic Substances Control Act) inventory
Nickel (7440-02-0) Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings) SARA Section 313 - Emission Reporting: 0.1%	Vanadium pentoxide (1314-62-1) Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 302 (Specific toxic chemical listings) SARA Section 302 Threshold Planning Quantity (TPQ): ≤ 10000
Molybdenum (7439-98-7) Listed on the United States TSCA (Toxic Substances Control Act) inventory	Titanium dioxide (13463-67-7) Listed on the United States TSCA (Toxic Substances Control Act) inventory
Calcium fluoride (CaF₂) (7789-75-5) Listed on the United States TSCA (Toxic Substances Control Act) inventory	Sodium silicate (1344-09-8) Listed on the United States TSCA (Toxic Substances Control Act) inventory
Potassium silicate (1312-76-1) Listed on the United States TSCA (Toxic Substances Control Act) inventory	Calcium carbonate (1317-65-3) Listed on the United States TSCA (Toxic Substances Control Act) inventory
Titanate, dipotassium (12030-97-6) Listed on the United States TSCA (Toxic Substances Control Act) inventory	Magnesium oxide (1309-48-4) Listed on the United States TSCA (Toxic Substances Control Act) inventory
Silica, crystalline (14808-60-7) Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2 US State regulations

Nickel (7440-02-0)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List		U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List		
Vanadium pentoxide (1314-62-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List		U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List		
Cobalt (7440-48-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List		U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List		
Titanium dioxide (13463-67-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List		U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List		
Silica, crystalline (14808-60-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List		U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List		
Chromium (7440-47-3)				
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List		Manganese (7439-96-5) U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List		



SAFETY DATA SHEET

Magnesium oxide (1309-48-4) U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	Aluminum (7429-90-5) U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Silicon (7440-21-3) U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	Titanium (7440-32-6) U.S. - New Jersey - Right to Know Hazardous Substance List
Molybdenum (7439-98-7) U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	Calcium carbonate (1317-65-3) U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Section 16 – OTHER INFORMATION


SUPERSEDES LAST REVISION: 10/22/2015 (SDS)

HMIS RATING (Hazardous Materials Information System)			
Health (blue) - 2	Flammability (red) - 0	Reactivity (yellow) - 0	Protective Equipment - X (See Sections 4, 8 & 10)

Health Hazard: 2 (moderate acute or significant chronic exposure hazard)
Flammability Hazard: 0 (minimal hazard)
Reactivity Hazard: 0 (normally stable)

NATIONAL FIRE PROTECTION ASSOCIATION:

Health Hazard: 0 (material that on exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials); 1 (materials that on exposure under fire conditions could cause irritation or minor residual injury); 2 (materials that on intense or continued exposure under fire conditions could cause temporary incapacitation or possible residual injury); 3 (materials that can on short exposure cause serious temporary or residual injury); 4 (materials that under very short exposure causes death or major residual injury).
Flammability Hazard: Refer to definitions for "HMIS RATING"
Reactivity Hazard: Refer to definitions for "HMIS RATING"



DEFINITIONS OF TERMS

- ACGIH - American Conference of Governmental Industrial Hygienists
- CAS No. - Chemical Abstracts Service Number
- EPA - Environmental Protection Agency
- GHS - Globally Harmonized System
- IARC - International Agency for Research on Cancer
- LC50 - Lethal Concentration (50 percent kill)
- LCLO - Lowest published lethal concentration
- LD50 - Lethal dose (50 percent kill)
- LDLO - Lowest published lethal dose
- NIOSH - National Institute of Occupational Safety and Health

- NTP - National Toxicology Program
- OSHA - U.S. Occupational Safety and Health Administration
- PEL - Permissible Exposure Limit
- SARA - Superfund Amendments and Reauthorization Act
- STEL - Short Term Exposure Limit
- TCLo - the lowest concentration to cause a symptom
- TDLo - the lowest dose to cause a symptom
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average

Full text of H-phrases (from Section 2)

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Carc. 1A	Carcinogenicity, Category 1A
Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
Repr. Tox. 2	Reproductive toxicity, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3
H302	Harmful if swallowed

H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H350	May cause cancer
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES: Crown Alloys Company urges each end user and recipient of this SDS to study it carefully. If necessary, consult an industrial hygienist or other expert to understand this information and safeguard the environment and protect workers from the potential hazards associated with the handling or use of this product. The information in this document is believed to be correct as of the date issued. However, this information is provided without any representation or warranty, expressed or implied, regarding accuracy or correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons we do not assume responsibility and expressly disclaim liability of loss, damage, or expense arising from it or any way connected with the handling, storage, use, or disposal of this product. Data may be changed from time to time. Be sure to consult the latest edition of the SDS. Compliance with all applicable Federal, State, Provincial and local laws and regulations remain the responsibility of the user.